

Material Safety Data Sheet

Carpet Prespray

1. Product and company identification

Product name	Carpet Prespray	In case of emergency	1-800-843-6174
Code	321CC	Validation date	11/8/2011.
Material uses	Liquid rug shampoo	Print date	11/8/2011.
Manufacturer	Essential Industries, Inc. P.O. Box 12 Merton, WI 53056-0012 Phone: 262-538-1122	Responsible name	Regulatory Affairs Department

Hazardous Material Information System (U.S.A.)

Health	1	HAZARD RATING
Flammability	0	4 = Extreme
Physical hazards	0	3 = High
Personal protection	B	2 = Moderate
		1 = Slight
		0 = Insignificant

A = Goggles B = Goggles & Gloves C = Goggles, Gloves & Apron

2. Hazards identification

Emergency overview WARNING!
HARMFUL IF INHALED OR SWALLOWED.
Harmful by inhalation and if swallowed. Do not breathe vapor or mist. Do not ingest. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Keep container tightly closed and sealed until ready for use. Wash thoroughly after handling.

Potential acute health effects due to overexposure

Inhalation Harmful by inhalation.
Ingestion Harmful if swallowed.
Skin Toxic in contact with skin. Slightly irritating to the skin.
Eyes Severely irritating to eyes. Risk of serious damage to eyes.

Potential chronic health effects due to overexposure

Carcinogenicity No known significant effects or critical hazards.
Mutagenicity No known significant effects or critical hazards.
Teratogenicity No known significant effects or critical hazards.
Developmental effects No known significant effects or critical hazards.
Fertility effects No known significant effects or critical hazards.

See toxicological information (section 8)

3. Composition/information on ingredients

Name	CAS number	%
ethylene glycol monobutyl ether	111-76-2	1 - 5

SARA 313 (Form R - Reporting requirements)

Product name	CAS number	Concentration
ethylene glycol monobutyl ether	111-76-2	2.2

SARA 313 notifications must not be detached from the MSDS and any copying and redistribution of the MSDS shall include copying and redistribution of the notice attached to copies of the MSDS subsequently redistributed.

4. First aid measures

Eye contact Check for and remove any contact lenses. Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting the upper and lower eyelids. Get medical attention immediately.

Skin contact In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash clothing before reuse. Clean shoes thoroughly before reuse. Get medical attention immediately.

Inhalation Move exposed person to fresh air. Loosen tight clothing such as a collar, tie, belt or waistband. Get medical attention immediately.

Ingestion Wash out mouth with water. Do not induce vomiting unless directed to do so by medical personnel. Get medical attention immediately.

Protection of first-aiders No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

Notes to physician No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

5. Fire-fighting measures

Flammability of the product	In a fire or if heated, a pressure increase will occur and the container may burst.
Extinguishing media	
Suitable	Use an extinguishing agent suitable for the surrounding fire.
Special exposure hazards	Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Hazardous thermal decomposition products	Decomposition products may include the following materials: carbon dioxide carbon monoxide sulfur oxides phosphorus oxides metal oxide/oxides
Special protective equipment for fire-fighters	Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
Flash point	Closed cup: Not applicable

6. Control and preventive measures

Storage	Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.
----------------	---

Ingredient	Exposure limits
ethylene glycol monobutyl ether	OSHA PEL (United States, 6/2010). Absorbed through skin. TWA: 50 ppm 8 hour(s). TWA: 240 mg/m ³ 8 hour(s). OSHA PEL 1989 (United States, 3/1989). Absorbed through skin. TWA: 25 ppm 8 hour(s). TWA: 120 mg/m ³ 8 hour(s). NIOSH REL (United States, 6/2009). Absorbed through skin. TWA: 5 ppm 10 hour(s). TWA: 24 mg/m ³ 10 hour(s). ACGIH TLV (United States, 2/2010). TWA: 20 ppm 8 hour(s).

Personal protection

Respiratory	None required. However, use of adequate ventilation is good industrial practice.
Hands	Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Skin	Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Eyes	Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

Methods for cleaning up

Small spill	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Waste disposal	Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

7. Physical and chemical properties

Physical state	Liquid	Boiling/condensation point	100°C (212°F)
Color	Green	Melting/freezing point	0°C (32°F)
Odor	Country Fresh	Vapor pressure	<4 kPa (<30 mm Hg) [20°C]
VOC	1.8%	Vapor density	<1 [Air = 1]
pH	9.5 to 10.5 (Use Dil. 9.3)	Weight per Gallon:	8.82 lbs./gal.
1% pH:	Not applicable	Specific Gravity:	1.06 gm/ml
Solubility	Complete		

8. Toxicological information

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
ethylene glycol monobutyl ether	LD50 Dermal	Rabbit	220 mg/kg	-
	LD50 Intraperitoneal	Rat	220 mg/kg	-
	LD50 Intravenous	Rat	307 mg/kg	-
	LD50 Oral	Rat	917 mg/kg	-
	LD50 Oral	Rat	250 mg/kg	-
	LD50 Unreported	Rat	917 mg/kg	-
	LDLo Oral	Rat	1500 mg/kg	-
	TDLo Oral	Rat	500 mg/kg	-
	TDLo Unreported	Rat	250 mg/kg	-

8. Toxicological information

LC50 Inhalation Vapor	Rat	2900 mg/m3	7 hours
LC50 Inhalation Gas.	Rat	450 ppm	4 hours

[Conclusion/Summary](#) Not available

[Chronic toxicity](#)

[Conclusion/Summary](#) Not available

9. Transport information

Regulatory information	UN number	Proper shipping name	Classes	PG*	Label	Additional information
DOT Classification	Not regulated	-	-	-		-

PG* : Packing group