

SAFETY DATA SHEET

DRY FOAM CARPET SHAMPOO

1. Identification of the substance/preparation and of the company/undertaking

Identification of the substance or preparation

Product name : DRY FOAM CARPET SHAMPOO

Product No. : 00314CC

Use of the substance/preparation : Dry foam rug shampoo

Company/undertaking identification

Manufacturer : Essential Industries, Inc.
P.O. Box 12
28391 Essential Rd.
Merton, WI 53056-0012 USA

Supplier : Essential Industries, Inc.
P.O. Box 12
28391 Essential Rd.
Merton, WI 53056-0012 USA

Emergency telephone number : 001-262-821-7814

2. Composition/information on ingredients

Substance/Preparation : Preparation

Ingredient Name	CAS number	%	EC Number	Classification
2-butoxyethanol	111-76-2	10-15	203-905-0	Xn; R20/21/22 Xi; R36/38
sodium dodecyl sulfate	151-21-3	5-10	205-788-1	Xn; R22
propan-2-ol	67-63-0	1-5	200-661-7	F; R11 Xi; R36 R67
See Section 16 for the full text of the R Phrases declared above				

* Occupational Exposure Limit(s), if available, are listed in section 8

3. Hazards identification

The preparation is not classified as dangerous according to Directive 1999/45/EC and its amendments.

See Section 11 for more detailed information on health effects and symptoms.

4. First aid measures

First aid measures

Inhalation : If inhaled, remove to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Get medical attention.

Ingestion : Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If large quantities of this material are swallowed, call a physician immediately.

Skin contact : In case of contact, immediately flush skin with plenty of water. Remove contaminated clothing and shoes. Wash clothing before reuse. Thoroughly clean shoes before reuse. Get medical attention.

Eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation occurs.

Specific treatments : None identified.

See Section 11 for more detailed information on health effects and symptoms.

DRY FOAM CARPET SHAMPOO

5. Fire-fighting measures

- Extinguishing media** : In case of fire, use water spray (fog), foam, dry chemical, or CO₂.
- Special exposure hazards** : No specific hazard.
Not available.
- Hazardous thermal decomposition products** : These products are carbon oxides (CO, CO₂), sulfur oxides (SO₂, SO₃...). Some metallic oxides.
- Special protective equipment for fire-fighters** : Fire-fighters should wear positive pressure self-contained breathing apparatus (SCBA) and full turnout gear.

6. Accidental release measures

- Personal precautions** : Immediately contact emergency personnel. Keep unnecessary personnel away. Use suitable protective equipment (Section 8). Follow all fire fighting procedures (Section 5).
- Environmental Precautions and Clean-up Methods** : Minimize contact of spilled material with soils to prevent runoff to surface waterways. See Section 13 for Waste Disposal Information.
If emergency personnel are unavailable, contain spilled material. For small spills add absorbent (soil may be used in the absence of other suitable materials) scoop up material and place in a sealed, liquid-proof container for disposal. For large spills dike spilled material or otherwise contain material to ensure runoff does not reach a waterway. Place spilled material in an appropriate container for disposal.

Note: See section 8 for personal protective equipment and section 13 for waste disposal.

7. Handling and storage

- Handling** : Wash thoroughly after handling.
- Storage** : Keep container tightly closed. Keep container in a cool, well-ventilated area.
- Packaging materials**
- Recommended** : Use original container.
- Specific uses** : Industrial applications

8. Exposure controls/personal protection

<u>Ingredient Name</u>	<u>Occupational Exposure Limits</u>
2-butoxyethanol	EH40-OES (United Kingdom (UK), 2002). Skin STEL: 50 ppm 15 minute(s). TWA: 25 ppm 8 hour(s).
propan-2-ol	EH40-OES (United Kingdom (UK), 2002). STEL: 1250 mg/m ³ 15 minute(s). STEL: 500 ppm 15 minute(s). TWA: 999 mg/m ³ 8 hour(s). TWA: 400 ppm 8 hour(s).

- Recommended monitoring procedures** : Good general ventilation should be sufficient to control airborne levels.
- Exposure controls**
- Occupational exposure controls** : Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective occupational exposure limits. Ensure that eyewash stations and safety showers are proximal to the work-station location.
- Respiratory protection** : A respirator is not needed under normal and intended conditions of product use.
- Hand protection** : Use latex gloves.
- Eye protection** : Safety glasses.
- Skin protection** : Additional body garments should be used based upon the task being performed (e.g., sleevelets, apron, gauntlets, disposable suits).

9. Physical and chemical properties

General information

Appearance

- Physical state** : Liquid.
Color : Aqua.
Odor : Citrus.

Important health, safety and environmental information

- pH** : 6.2-7.1
Boiling Point : The lowest known value is 82.55°C (180.6°F) (propan-2-ol). Weighted average: 109.05°C (228.3°F)
Melting Point : May start to solidify at 204.06 to 207.06°C (399.3 to 404.7°F) based on data for: sodium dodecyl sulfate. Weighted average: 3.48°C (38.3°F)
Flash point : The lowest known value is Open cup: 11.9°C (53.4°F). (propan-2-ol)
Flammability (solid, gas) : Not applicable.
Explosive properties : Risks of explosion of the product in presence of mechanical impact: Not available.
Risks of explosion of the product in presence of static discharge: Not available.
Oxidizing Properties : Not available.
Relative density : Weighted average: 0.98 g/cm³
Solubility : Easily soluble in cold water, hot water, methanol, acetone.
Vapor Density : The highest known value is 4.07 (Air = 1) (2-butoxyethanol). Weighted average: 3.68 (Air = 1)
Evaporation rate (butyl acetate = 1) : The highest known value is 1.7 (propan-2-ol) Weighted average: 0.36 compared to Butyl acetate.

Other information

- Auto-ignition temperature** : The lowest known value is 244.05°C (471.3°F) (2-butoxyethanol).

10. Stability and reactivity

- Stability** : The product is stable.
Conditions to avoid : None identified.
Materials to avoid : None identified.
Hazardous decomposition products : These products are carbon oxides (CO, CO₂), sulfur oxides (SO₂, SO₃...). Some metallic oxides.

11. Toxicological information

Potential Acute Health Effects

- Inhalation** : May cause respiratory tract irritation.
Ingestion : May irritate digestive tract.
Skin contact : Prolonged or repeated contact may dry skin and cause irritation.
Eye contact : Direct contact may cause irritation and redness.

Acute toxicity

<u>Ingredient Name</u>	<u>Test</u>	<u>Result</u>	<u>Route</u>	<u>Species</u>
2-butoxyethanol	LD50	470 mg/kg	Oral	Rat
	LD50	300 mg/kg	Oral	Rabbit
	LD50	1200 mg/kg	Oral	Guinea pig
	LD50	220 mg/kg	Dermal	Rabbit
sodium dodecyl sulfate	LD50	1288 mg/kg	Oral	Rat
	LD50	5045 mg/kg	Oral	Rat
propan-2-ol	LD50	6410 mg/kg	Oral	Rabbit
	LD50	3600 mg/kg	Oral	Mouse
	LD50	12800 mg/kg	Dermal	Rabbit
	LDLo	1537 mg/kg	Oral	Dog
	LDLo	3570 mg/kg	Oral	human
	LDLo	5272 mg/kg	Oral	man

- Carcinogenicity** : No carcinogenic effect known.

DRY FOAM CARPET SHAMPOO

Mutagenicity : No mutagenic effect.

Reproductive toxicity : No teratogenic effect.

Over-exposure signs/symptoms

Target Organs : Contains material which causes damage to the following organs: blood, kidneys, liver, lymphatic system, upper respiratory tract, skin, central nervous system (CNS), eye, lens or cornea.

Other adverse effects : Not available.

12. Ecological information

Ecotoxicity Data

<u>Ingredient Name</u>	<u>Species</u>	<u>Period</u>	<u>Result</u>
2-butoxyethanol	Lepomis macrochirus (LC50)	96 hour(s)	1490 mg/l
	Daphnia magna (EC50)	48 hour(s)	6 mg/l
sodium dodecyl sulfate	Daphnia magna (EC50)	48 hour(s)	31 mg/l
	Selenastrum capricornutum (EC50)	48 hour(s)	104.8 mg/l
propan-2-ol	Cyprinus carpio (LC50)	96 hour(s)	1.31 mg/l
	Lepomis macrochirus (LC50)	96 hour(s)	4.5 mg/l
	Oncorhynchus mykiss (LC50)	96 hour(s)	4.62 mg/l
	Pimephales promelas (EC50)	48 hour(s)	10000 mg/l
	Lepomis macrochirus (LC50)	96 hour(s)	>1400 mg/l
	Pimephales promelas (LC50)	96 hour(s)	6550 mg/l
	Pimephales promelas (LC50)	96 hour(s)	9640 mg/l
	Pimephales promelas (LC50)	96 hour(s)	10400 mg/l
	Pimephales promelas (LC50)	96 hour(s)	11130 mg/l

Mobility : Not available.

Other adverse effects : Not available.

13. Disposal considerations

Methods of disposal : Avoid contact of spilled material and runoff with soil and surface waterways. Dispose of according to all federal, state and local applicable regulations.

Waste Classification : Not applicable.

European Waste Catalogue (EWC) : Not available.

Hazardous Waste : To present knowledge of the supplier, this product is not regarded as hazardous waste as defined by EU Directive 91/689/EC.

14. Transport information

International transport regulations

<u>Regulatory information</u>	<u>UN number</u>	<u>Proper shipping name</u>	<u>Class</u>	<u>Packing Group</u>	<u>Label</u>	<u>Additional information</u>
ADR/RID Class	Not Regulated.	-	-	-		-
ADN Class	Not Regulated.	-	-	-		-
IMDG Class	Not Regulated.	-	-	-		-
IATA-DGR Class	Not Regulated.	-	-	-		-

15. Regulatory information

EU Regulations

Hazard symbol(s)

:



Risk phrases

: This product is not classified according to the EU regulations.

Safety phrases

: No specific safety phrase has been found applicable for this product.

Product Use

: Classification and labeling have been performed according to EU directives 67/548/EEC, 1999/45/EC including amendments and the intended use.
- Industrial applications.

Additional Warning Phrases

: Safety Data Sheet available for professional user on request.

EC Statistical Classification

: 32089091

(Tariff Code)

National regulations

16. Other information

Full text of R phrases referred to in Sections 2 and 3 - United Kingdom (UK)

: R11- Highly flammable.
R20/21/22- Harmful by inhalation, in contact with skin and if swallowed.
R22- Harmful if swallowed.
R36- Irritating to eyes.
R36/38- Irritating to eyes and skin.
R67- Vapors may cause drowsiness and dizziness.

Full text of classifications referred to in Sections 2 and 3 - United Kingdom (UK)

: F - Highly flammable
Xn - Harmful
Xi - Irritant

HISTORY

Date of printing

: 5/23/2005.

Date of issue

: 5/22/2005.

Date of Previous Issue

: No Previous Validation.

Version

: 1

Prepared by

: Regulatory Affairs.

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein.

Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.