

WOOD CLEAN

Environmentally-Responsible Floor Cleaner

FEATURES

- No-rinse cleaner designed for damp mopping or scrubbing of finished wood floors
- Also excellent for cleaning walls, equipment, resilient floors, display cases, furniture, etc.
- Neutral pH in 100%, 10% and 1% solution
- Non-flammable, non-toxic, non-corrosive and phosphate-free
- High biobased content (51%-90%)
- Slip-resistant - UL classified



High biobased content is defined by products containing 51% - 90% ingredients made from renewable plant, animal or marine resources per the Biobased Manufacturers Association.



PROPERTIES*

Type.....	Synthetic Detergent
Form	Clear Liquid
Odor.....	Fresh
Color	Green
Weight per Gallon	8.41 Lbs.
pH	7.8
pH 1%	7.0
Storage Stability	Min. 1 Year
Freeze/Thaw.....	Passes 3 Cycles

* Properties are typical and subject to usual manufacturing tolerances



Merton, Wisconsin 53056-0012 USA
Phone: (262) 538-1122
www.essind.com



1143SF



WOOD CLEAN

Environmentally-Responsible Floor Cleaner

PRODUCT SAFETY AND TRAINING

DISPOSAL - APPLICATION - FIRST AID

Environmentally preferable formula is non-flammable, non-toxic, noncorrosive and phosphate-free. Neutral pH in 100%, 10% and 1% solutions.

DISPOSAL

PRODUCT: Dispose of in accordance with local authority regulations.

CONTAINER: Made from HDPE and should be disposed of in accordance with local authority regulations. Please recycle.

IMPROPER USE OR APPLICATION

IMPROPER USE: May irritate eyes, skin and gastrointestinal tract. Avoid eye and skin contact.

IMPROPER APPLICATION: Under dilution may affect product performance. Over dilution may leave a residue.

FIRST AID

EYES & SKIN: Flush with water (eyes 15 minutes). If irritation persists, seek medical attention.

INGESTION: If swallowed, give 2-3 large glasses of water. Seek medical attention.

CONCENTRATE DIRECTIONS

- Damp Mopping.....dilute 2 ounces per gallon (1:64).
- Automatic Scrubbingdilute 2 ounces per gallon (1:64).
- All Purpose Cleaning.....dilute 2-4 ounces per gallon (1:32 -1:64).



NOTE: Dilute with cold water.

NOTE: For stripping and maintaining asbestos containing tile, follow OSHA or EPA guidelines.

READY-TO-USE DIRECTIONS

The ready-to-use solution has already been properly diluted.

1. Fill mop bucket or auto-scrubber with properly diluted product.
2. Clean floor using a minimal amount of product - do not let cleaner sit on floor.



CAUTION: Avoid saturating wood floors with cleaning solution. Be sure mops are thoroughly wrung out and auto-scrubbers are in good working order. Do not use on unfinished or poorly finished wood floors.

- No-rinse cleaner designed for damp mopping or scrubbing of finished wood floors.
- Also excellent for cleaning walls, equipment, resilient floors, display cases, furniture, etc.



Merton, Wisconsin 53056-0012 USA
Phone: (262) 538-1122
www.essind.com



Floor Coating and Finishing Material. As to Slip Resistance Only. 177S

© 2011 Essential Industries, Inc. 10111
LT-90000S1143SF