

GROUT Restoration SYSTEM

A fully-loaded grout system engineered to specifically target, remove and then lock out the dirt and soils that make grout so difficult to maintain.



GROUT AVENGER Cleans - Whitens - Maintains

Special formulation designed to target and break down water scale, soap scum, bodily fluids and soils while "lifting" it out of the grout.

- Safe for use on all grouted tile floors
- Includes malodor counteractant package to eliminate odor
- Will not stain grout or tile
- Use for periodic heavy cleaning or regular maintenance
- No special equipment needed

GPS Grout Penetrating Sealer

A tough, high solid, water-borne sealer that penetrates deep into grout and repels soil and germs while improving slip resistance.

- Dual cross-linking polymer makes this seal ultra-durable against wear and soil penetration
- Highly resistant to acids, bases and stains
- High solids formula fills pores in grouted surfaces
- Meets or exceeds VOC regulations in all 50 states
- Improves traction on floor to decrease slips and falls

GROUT AVENGER

Grout Avenger quickly penetrates and releases the toughest soils from grout lines and stone surfaces. It removes body oils, soap scum, grease, ground in grime and mildew. Use it on shower floors and walls, restroom floors and walls, kitchen floors and other areas with grouted surfaces. Grout Avenger can be used on ceramic, terrazzo, brick pavers, slate and granite.

DIRECTIONS

Dilute with water (see below). Apply with a mop or sprayer. Let stand for 10 minutes and agitate with a brush. Pick up excess solution and rinse well with water.

HEAVY SOIL: Dilute 1:4 (32 ounces per gallon).

MODERATE SOIL: Dilute 1:8 (16 ounces per gallon).

LIGHT SOIL: Dilute 1:32 (4 ounces per gallon).

NOTE: Do not use on marble or soft stone.

GPS - Grout Penetrating Sealer

GPS Grout Penetrating Sealer actively disperses deep into the grout and seals out soils and stains. The heart of this powerful water-based sealer is a dual cross-linking polymer which makes the sealer ultra-durable and highly resistant to acids, bases and stains. GPS is VOC compliant in all 50 states and improves the floor's slip resistance.

Application: Read all directions and warnings on package before using.

NOTE: Apply a small amount in an inconspicuous area to assure compatibility with surface to be treated, and to confirm satisfactory results. Wait a minimum of 24 hours to determine suitability.

For New Grout: Be sure grout is dry before sealing. Wait 48 hours after grouting to seal.

For Existing Grout:

1. Ensure the surface is clean by using #2085 Blue Concentrate and then allow to dry. Existing sealers and coatings should be removed with #2917 Xlerate Stripper prior to coating.
2. Apply 1 to 3 coats of GPS. Apply with a foam brush, grout sealer applicator, brush, cloth or roller.
3. Wipe up excess sealer where pools remain. Do not allow product to dry on tile surface.
4. 5-10 minutes after last application, wipe all sealer from the surfaces of tile and stones, not allowing it to dry on them.
5. Surface is ready for traffic in 2 hours. Keep area dry for at least 12 hours: cures completely in 24 hours.

Coverage: Approximately 2,000 sq. ft. per gallon for one coat, depending on porosity, texture, temperature, humidity and method of application.

Wear: Test for absorption periodically and reseal when water starts to absorb.

Limits: Do not use below 55 degrees F.