

www.essind.com

Durabrite® LE

Low Maintenance Finish

Features

- Low emission formula – meets new 1% VOC Regulation
- Extremely durable and mark-resistant finish for low maintenance applications
- High gloss acrylic polymers stay clean, clear, and shiny to reduce maintenance
- Non-yellowing, low maintenance formula offers superb black mark and scuff resistance
- Ideal for reduced burnishing programs (once per week)
- Use on vinyl tile, rubber, linoleum, terrazzo and quarry tile floors
- Excellent seal properties
- Fast-drying – 20 to 30 minutes under normal conditions
- Fast-curing – 2 hours under normal conditions
- Slip-resistant – UL Classified

Properties

Type..... Metal-Interlocked Acrylic
Form..... Opaque Liquid
Odor..... Bland
Color..... Milky White
Film Clarity..... Clear
Weight per Gallon..... 8.60 Lbs
pH..... 8.1 - 8.3
Floor Solids..... 18%
Storage Stability..... Min. 1 Year
Freeze/Thaw..... Passes 3 Cycles
V.O.C..... <45 gm/l



* Properties are typical and subject to usual manufacturing tolerances



Scan QR code for access to more product information and Safety Data Sheet.

73FF



ESSENTIAL
INDUSTRIES

P.O. Box 12
Merton, Wisconsin 53056
Phone: (262) 538-1122
www.essind.com

© 2016 Essential Industries, Inc. J2515

Lit. # LT-9000S0073FF