

www.essind.com

Durabrite® HS LE

High Solids Finish

Features

- Low emission formula – meets new 1% VOC Regulation
- High solids formula offers greater protection with fewer coats
- Non-yellowing, low maintenance, scuff-resistant formula is ideal for areas where buffing is not performed
- Perfect for classrooms, patient rooms, offices, etc.
- Large area coverage – up to 3,000 sq. ft. per gallon
- Fast-drying – 30 minutes under normal conditions
- Slip-resistant – UL classified

Properties

Type..... Metal-Interlocked Acrylic
Form..... Opaque Liquid
Odor..... Bland
Color..... Milky White
Film Clarity..... Clear
Weight per Gallon..... 8.63 Lbs
pH..... 7.8 - 8.4
Floor Solids..... 22%
Storage Stability..... Min. 1 Year
Freeze/Thaw..... Passes 3 Cycles
V.O.C..... <45 gm/l



* Properties are typical and subject to usual manufacturing tolerances



Scan QR code for access to more product information and Safety Data Sheet.

75FF



ESSENTIAL
INDUSTRIES

P.O. Box 12
Merton, Wisconsin 53056
Phone: (262) 538-1122
www.essind.com

© 2016 Essential Industries, Inc. J2515

Lit. # LT-90000S0075FF