

[www.xcoatnano.com](http://www.xcoatnano.com)

# X-Coat™ Nano

## Extreme Performance Coating

### Patented Nano-Zinc Technology

U.S. Patent No. 8,236,903

### Features

- Incorporates our patented nano-zinc technology for more thorough and denser cross-linking of finish.
- Nano-zinc cross-linking provides superior:
  - Lay-down gloss
  - Durability
  - Soil resistance
  - Gloss build
  - Mark resistance
  - Dry and recoat times
- Ammonia-free for dramatically reduced odor.
- Ideal for limited maintenance programs, yet responds to daily burnishing, if desired.
- Low emissions formula - meets California's new 1% VOC Regulation.
- Fast-drying - 15-20 minutes under normal conditions.
- Slip-resistant - UL-classified

**NANO**  
technology

### Properties

Type.....	Acrylic Emulsion
Form.....	Opaque Liquid
Odor.....	Bland
Color.....	Milky White
Film Clarity.....	Clear
Weight Per Gallon.....	8.57 Lbs.
pH.....	8.0 - 8.5
Floor Solids.....	20%
Storage Stability.....	Minimum 1 Year
Freeze/Thaw.....	Protect From Freezing
V.O.C.....	0.59%

\* Properties are typical and subject to usual manufacturing tolerances



Scan QR code for access to more product information and Safety Data Sheet.

88FF



**ESSENTIAL**  
**INDUSTRIES**

P.O. Box 12  
Merton, Wisconsin 53056  
Phone: (262) 538-1122  
[www.essind.com](http://www.essind.com)

© 2015 Essential Industries, Inc. H0615

Lit. # LT-9000S0088FF