

www.essind.com

Pureshine™ 25

High Solids, High Gloss Finish

Features

- All purpose, all system high solids finish with extreme lay-down gloss
- Exceptional long-term gloss and wear
- 25% high solids formula offers greater protection with fewer coats
- Non-yellowing, low maintenance, scuff-resistant formula is ideal for areas where frequent buffing is not performed
- Use in schools, offices, hospitals, retail stores, lobbies
- Large area coverage – up to 3,000 sq. ft. per gallon
- Fast-drying – 30 to 40 minutes under normal conditions
- Slip-resistant – UL classified

Properties

Type	Acrylic Emulsion
Form	Opaque Liquid
Odor	Bland
Color	Milky White
Film Clarity	Clear
Weight per Gallon	8.65 Lbs.
pH	7.6 - 8.6
Floor Solids	25%
Storage Stability	Min. 1 Year
Freeze/Thaw	Passes 3 Cycles
V.O.C.	<270 gm/l



* Properties are typical and subject to usual manufacturing tolerances



Scan QR code for access to more product information and Safety Data Sheet.

216FF



ESSENTIAL[®]
INDUSTRIES

P.O. Box 12
Merton, Wisconsin 53056
Phone: (262) 538-1122
www.essind.com

© 2015 Essential Industries, Inc. H0615

Lit. # LT-90000S0216FF