

www.essind.com

Durabrite®

Low Maintenance Finish

Features

- Extremely durable and mark-resistant finish for low maintenance applications
- High gloss acrylic polymers stay clean, clear, and shiny to reduce maintenance
- Non-yellowing, low maintenance formula offers superb black mark and scuff resistance
- Ideal for reduced burnishing programs (once per week)
- Use on vinyl tile, rubber, linoleum, terrazzo and quarry tile floors
- Excellent seal properties
- Fast-drying – 20 to 30 minutes under normal conditions
- Fast-curing – 2 hours under normal conditions
- Slip-resistant – UL Classified

Properties

Type	Metal-Interlocked Acrylic
Form	Opaque Liquid
Odor	Bland
Color	Milky White
Film Clarity	Clear
Weight per Gallon	8.60 Lbs
pH	8.1 - 8.3
Floor Solids	18%
Storage Stability	Min. 1 Year
Freeze/Thaw	Passes 3 Cycles
V.O.C.	<260 gm/l



* Properties are typical and subject to usual manufacturing tolerances



Scan QR code for access to more product information and Safety Data Sheet.

253FF



ESSENTIAL
INDUSTRIES

P.O. Box 12
Merton, Wisconsin 53056
Phone: (262) 538-1122
www.essind.com

© 2015 Essential Industries, Inc. H0615

Lit. # LT-90000S0253FF