

www.xcoatnano.com

X-Coat™

Extreme Performance Coating

Features

- Combines deep gloss, high durability and ease-of-use into one product
- High gloss acrylic polymers produce a beautiful, long-lasting shine to reduce maintenance
- Perfect for classrooms, patient rooms, offices and retail establishments
- Ideal for limited maintenance programs, yet responds to daily burnishing, if desired
- Fast drying – 30 minutes under normal conditions
- Use on vinyl, rubber, linoleum, terrazzo, quarry tile and sealed concrete floors
- Slip-resistant – UL-classified

Properties

Type Acrylic Emulsion
Form Opaque Liquid
Odor Bland
Color Milky White
Film Clarity Clear
Weight Per Gallon 8.57 Lbs.
pH 8.0 - 8.5
Floor Solids 18%
Storage Stability Min. 1 Year
Freeze/Thaw Passes 3 Cycles
V.O.C. <230 gm/l

* Properties are typical and subject to usual manufacturing tolerances



Scan QR code for access to more product information and Safety Data Sheet.

264FF



 **ESSENTIAL®**
INDUSTRIES

P.O. Box 12
Merton, Wisconsin 53056
Phone: (262) 538-1122
www.essind.com

© 2015 Essential Industries, Inc. H0615

Lit. # LT-90000S0264FF