

[www.essind.com](http://www.essind.com)

# Stonethane™

## Concrete and Stone Finish

### Features

- Tough urethane seal/finish for use on all stone and concrete floors
- Durable, urethane finish protects stone and concrete floors from wear and simplifies maintenance
- Excellent chemical resistance
- Large area coverage – up to 2,500 sq. ft. per gallon
- Fast-drying – 30 to 45 minutes under normal conditions
- Responds to high-speed buffing
- Slip-resistant – UL classified

### Properties

Type..... Urethane / Acrylic Emulsion  
Form..... Opaque Liquid  
Odor..... Bland  
Color..... Milky White  
Film Clarity..... Clear  
Weight per Gallon..... 8.58 Lbs.  
pH..... 8.4 - 8.9  
Floor Solids..... 17%  
Storage Stability..... Min. 1 Year  
Freeze/Thaw..... Protect From Freezing  
V.O.C..... <390 gm/l



\* Properties are typical and subject to usual manufacturing tolerances



Scan QR code for access to more product information and Safety Data Sheet.

268FF



**ESSENTIAL**  
**INDUSTRIES**

P.O. Box 12  
Merton, Wisconsin 53056  
Phone: (262) 538-1122  
[www.essind.com](http://www.essind.com)

© 2015 Essential Industries, Inc. H0615

Lit. # LT-90000S0268FF