

[www.essind.com](http://www.essind.com)

# Eccothane™

## All Purpose Urethane Finish

### Features

- Multi-surface, all-purpose urethane-fortified finish for all maintenance systems
- Easy-to-use formula, adheres to most surfaces, levels nice and dries fast
- Urethane-fortified for maximum durability and beauty
- Combination seal and finish
- Large area coverage – up to 3,000 sq. ft. per gallon
- Fast-drying – 30 minutes under normal conditions
- Slip-resistant – UL classified

### Properties

Type.....	Urethane / Acrylic Emulsion
Form.....	Opaque Liquid
Odor.....	Bland
Color.....	Milky White
Film Clarity.....	Clear
Weight per Gallon.....	8.54 Lbs.
pH.....	8.2 - 8.6
Floor Solids.....	18%
Storage Stability.....	Min. 1 Year
Freeze/Thaw.....	Passes 3 Cycles
V.O.C.....	<300 gm/l



\* Properties are typical and subject to usual manufacturing tolerances



Scan QR code for access to more product information and Safety Data Sheet.

274FF



**ESSENTIAL**  
**INDUSTRIES**

P.O. Box 12  
Merton, Wisconsin 53056  
Phone: (262) 538-1122  
[www.essind.com](http://www.essind.com)

© 2015 Essential Industries, Inc. H0615

Lit. # LT-90000S0274FF