

# Acrylic Undercoater-Sealer

## Semi-Permanent Base Coat

### FEATURES

- Penetrates, levels and protects porous floors such as concrete, marble and terrazzo
- Also suitable for use on old, over-stripped resilient floors
- Large area coverage – Up to 2,000 sq. ft. per gallon
- Will not discolor with age
- Semi-permanent formula makes it ideal for sealing vinyl asbestos tiles
- Fast-drying – 30 to 40 minutes under normal conditions
- Meets ASTM D2047 Method for slip resistance

### PROPERTIES

**Type:** Acrylic Emulsion

**Form:** Opaque Liquid

**Odor:** Bland

**Color:** Milky White

**pH:** 9.2 - 9.6

**V.O.C.:** <270 gm/l

**Weight per Gallon:** 8.49 Lbs


**Storage Stability:** Min. 1 Year

**Freeze/Thaw:** Passes 3 Cycles

**Film Clarity:** Clear

**Floor Solids:** 17%

Properties are typical and subject to usual manufacturing tolerances



## 272SS

© 2022 Essential Industries, Inc. E1922  
Lit. # LT-90000S272SS



Scan QR code  
for access to more  
product information  
and Safety Data Sheet.

 **ESSENTIAL<sup>®</sup>**  
**INDUSTRIES**

**P.O. Box 12**  
**Merton, Wisconsin 53056**  
**Phone: (262) 538-1122**  
**www.essind.com**