

www.essind.com

Acrylic Undercoater-Sealer

Semi-Permanent Base Coat

Features

- Penetrates, levels and protects porous floors such as concrete, marble and terrazzo
- Also suitable for use on old, over-stripped resilient floors
- Large area coverage – Up to 2,000 sq. ft. per gallon
- Will not discolor with age
- Semi-permanent formula makes it ideal for sealing vinyl asbestos tiles
- Fast-drying – 30 to 40 minutes under normal conditions
- Slip-resistant – UL classified

Properties

Type..... Acrylic Emulsion
Form..... Opaque Liquid
Odor..... Bland
Color..... Milky White
Film Clarity..... Clear
Weight per Gallon..... 8.49 Lbs.
pH..... 9.2 - 9.6
Floor Solids..... 17%
Storage Stability..... Min. 1 Year
Freeze/Thaw..... Passes 3 Cycles
V.O.C..... <270 gm/l



* Properties are typical and subject to usual manufacturing tolerances



Scan QR code for access to more product information and Safety Data Sheet.

272SS



ESSENTIAL
INDUSTRIES

P.O. Box 12
Merton, Wisconsin 53056
Phone: (262) 538-1122
www.essind.com

© 2015 Essential Industries, Inc. H0615

Lit. # LT-90000S0272SS