

Acrylic Undercoater-Sealer

Semi-Permanent Base Coat

FEATURES

- Penetrates, levels and protects porous floors such as concrete, marble and terrazzo
- Also suitable for use on old, over-stripped resilient floors
- Large area coverage – Up to 2,000 sq. ft. per gallon
- Will not discolor with age
- Semi-permanent formula makes it ideal for sealing vinyl asbestos tiles
- Fast-drying – 30 to 40 minutes under normal conditions
- Slip-resistant – UL classified

PROPERTIES

Type: Acrylic Emulsion

Form: Opaque Liquid

Odor: Bland

Color: Milky White

pH: 9.2 - 9.6

V.O.C.: <270 gm/l

Weight per Gallon: 8.49 Lbs


Storage Stability: Min. 1 Year

Freeze/Thaw: Passes 3 Cycles

Film Clarity: Clear

Floor Solids: 17%

Properties are typical and subject to usual manufacturing tolerances



272SS

© 2021 Essential Industries, Inc. A1521
Lit. # LT-90000S272SS



Scan QR code
for access to more
product information
and Safety Data Sheet.

 **ESSENTIAL[®]**
INDUSTRIES

P.O. Box 12
Merton, Wisconsin 53056
Phone: (262) 538-1122
www.essind.com