

Durabrite®

Low Maintenance Finish

FEATURES


- Extremely durable and mark-resistant finish for low maintenance applications
- High gloss acrylic polymers stay clean, clear, and shiny to reduce maintenance
- Non-yellowing, low maintenance formula offers superb black mark and scuff resistance
- Ideal for reduced burnishing programs (once per week)
- Use on vinyl tile, rubber, linoleum, terrazzo and quarry tile floors
- Excellent seal properties
- Fast-drying – 20 to 30 minutes under normal conditions
- Fast-curing – 2 hours under normal conditions
- Slip-resistant – UL Classified

PROPERTIES

Type: Metal-Interlocked Acrylic
Form: Opaque Liquid
Odor: Bland
Color: Milky White
pH: 8.1 - 8.3
V.O.C.: <260 gm/l

Weight per Gallon: 8.60 Lbs
Storage Stability: Min. 1 Year
Freeze/Thaw: Passes 3 Cycles
Film Clarity: Clear
Floor Solids: 18%

Properties are typical and subject to usual manufacturing tolerances



253FF

© 2021 Essential Industries, Inc. B0821
Lit. # LT-90000S253FF



Scan QR code
for access to more
product information
and Safety Data Sheet.



P.O. Box 12
Merton, Wisconsin 53056
Phone: (262) 538-1122
www.essind.com