



This product meets Green Seal™ Standard GS-40 based on effective performance and protective limits on VOCs and human & environmental toxicity. GreenSeal.org.




Scan QR code for access to more product information and Safety Data Sheet.

8201FF

© 2017 Essential Industries, Inc. G1717
LT-9000S8201FF

G2 Green Finish

High Performance Floor Coating



Features

- Not formulated with butyl, harsh alkalis, zinc, phthalates or APEO surfactants
- Ultra-low 1.0% VOC content meets California's new 2011 standard
- Low odor - ammonia-free
- Multi-surface, all-purpose formula for all maintenance systems
- Easy-to-apply, levels nicely and dries to a high gloss
- Combination seal and finish
- Large area coverage – up to 3,000 sq. ft. per gallon
- Fast-drying – 20 minutes under normal conditions
- Slip-resistant – UL classified

Properties*

Type	Acrylic Emulsion
Form	Opaque Liquid
Odor	Bland
Color	Milky White
Film Clarity	Clear
Weight Per Gallon	8.61 Lbs.
pH	7.1
Floor Solids	20%
Storage Stability	Min. 1 Year
Freeze/Thaw	Do Not Freeze
V.O.C.	1.0%


* Properties are typical and subject to usual manufacturing tolerances

Green Essence™



This product meets Green Seal™ Standard GS-40 based on effective performance and protective limits on VOCs and human & environmental toxicity. GreenSeal.org.

G2 Green Finish High Performance Floor Coating



TRAINING

Directions

APPLICATION:

1. Strip floors to remove old waxes, sealers and finishes.
2. Rinse thoroughly and let dry.
3. With clean equipment apply thin, even coats of G2 Green Finish.
4. Under normal conditions, allow to dry for 20 minutes between coats.
5. For best results, apply a maximum of 4 coats in 24 hours.
6. Allow 48 hours for the finish to reach full cure before wet cleaning.
Burnishing will speed cure time.

NOTE: For stripping and maintaining asbestos containing tile, follow OSHA or EPA guidelines.

NOTE: DO NOT FREEZE

COVERAGE: One gallon covers up to 3,000 square feet.

MAINTENANCE:

Daily:

1. Sweep or dust mop frequently to remove gritty soil.
2. We recommend using a Green Seal™ certified floor cleaner to damp mop spills as they occur. Damp mop or auto-scrub nightly with a Green Seal™ certified floor cleaner.
3. Buff if desired with high speed equipment and blended hair pads.

Weekly:

1. To repair and deep clean floor, apply a green restorer with mop or auto-scrubber.
2. Allow floor to dry.
3. Burnish floor with high speed equipment. This finish also responds to spray buffing with conventional speed equipment.

Note: Always dust mop after burnishing or spray buffing.

Periodic Recoating:

1. Dust mop entire floor then scrub aggressively using a restorer and auto-scrubber with a red or green pad.
2. Rinse floor and allow to dry.
3. Apply G2 Green Finish.

Stripping G2 Green Finish: Strip with a Green Seal™ certified floor stripper.

Not formulated with butyl, harsh alkalies, zinc, phthalates or APEO surfactants.

DISPOSAL

PRODUCT: Dispose of excess product in accordance with local, state, and federal regulations.

CONTAINER: Please recycle container.

VENTILATION

No special ventilation needed. However, use of adequate ventilation is good industrial practice.

IMPROPER USE OR APPLICATION

IMPROPER USE: May irritate eyes, skin and gastrointestinal tract. Avoid eye and skin contact.

IMPROPER APPLICATION: Over application of finish may cause floor to be tacky, streaked and/or ghosted looking, dull and prone to black marking and scuffing.

Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Safety data sheet available on request.

See Product Safety Data Sheet Before Using.

Personal Protection Equipment

Gloves and Goggles



8201 FF

© 2017 Essential Industries, Inc. G1717

Merton, Wisconsin 53056-0012
Phone: (262) 538-1122
www.essind.com



ESSENTIAL®
INDUSTRIES