

RFS™

Resilient Floor Seal

FEATURES

- Adds Toughness, Builds Gloss and Extends The Life of All Finishes
- Penetrates, Levels and Protects All Resilient Floors Such as Vinyl, Vinyl Composition and Linoleum
- Also Suitable For Use On Old, Over-Stripped Asphalt Tile
- Large Area Coverage – Up to 2,500 Sq. Ft. per Gallon
- Strips Easily
- Fast-Drying – 30 Minutes Under Normal Conditions
- Slip-resistant – UL classified

PROPERTIES

Type: Acrylic Emulsion

Form: Opaque Liquid

Odor: Bland

Color: Milky White

pH: 8.0 - 8.5

V.O.C.: <260 gm/l

Weight per Gallon: 8.55 Lbs


Storage Stability: Min. 1 Year

Freeze/Thaw: Passes 3 Cycles

Film Clarity: Clear

Floor Solids: 15%

Properties are typical and subject to usual manufacturing tolerances



280SS

© 2021 Essential Industries, Inc. B1221
Lit. # LT-90000S280SS



Scan QR code
for access to more
product information
and Safety Data Sheet.

ESSENTIAL®
INDUSTRIES

P.O. Box 12
Merton, Wisconsin 53056
Phone: (262) 538-1122
www.essind.com