

www.essind.com



RFS™

Resilient Floor Seal

Features

- Adds Toughness, Builds Gloss and Extends The Life of All Finishes
- Penetrates, Levels and Protects All Resilient Floors Such as Vinyl, Vinyl Composition and Linoleum
- Also Suitable For Use On Old, Over-Stripped Asphalt Tile
- Large Area Coverage – Up to 2,500 Sq. Ft. per Gallon
- Strips Easily
- Fast-Drying – 30 Minutes Under Normal Conditions
- Slip-resistant – UL classified

Properties

Type Acrylic Emulsion
Form Opaque Liquid
Odor Bland
Color Milky White
Film Clarity Clear
Weight per Gallon 8.55 Lbs.
pH 8.0 - 8.5
Floor Solids 15%
Storage Stability Min. 1 Year
Freeze/Thaw Passes 3 Cycles
V.O.C. <260 gm/l

* Properties are typical and subject to usual manufacturing tolerances



Scan QR code for access to more product information and Safety Data Sheet.

280SS



ESSENTIAL®
INDUSTRIES

P.O. Box 12
Merton, Wisconsin 53056
Phone: (262) 538-1122
www.essind.com

© 2015 Essential Industries, Inc. H0615

Lit. # LT-90000S0280SS