www.essind.com

Durabrite® HS LE

High Solids Finish

FEATURES

- Low emission formula – meets new 1% VOC Regulation
- High solids formula offers greater protection with fewer coats
- Non-yellowing, low maintenance, scuff-resistant formula is ideal for areas where buffing is not performed
- Perfect for classrooms, patient rooms, offices, etc.
- Large area coverage – up to 3,000 sq. ft. per gallon
- Fast-drying – 30 minutes under normal conditions
- Slip-resistant – UL classified

PROPERTIES

Type: Metal-Interlocked Acrylic
Form: Opaque Liquid
Odor: Bland
Color: Milky White
pH: 7.8 - 8.4
V.O.C.: <45 gm/l

Weight per Gallon: 8.63 Lbs
Storage Stability: Min. 1 Year
Freeze/Thaw: Do Not Freeze
Film Clarity: Clear
Floor Solids: 22%

Properties are typical and subject to usual manufacturing tolerances

75FF

© 2021 Essential Industries, Inc. B0421
Lit. # LT-90000S75FF

Scan QR code for access to more product information and Safety Data Sheet.

ESSENTIAL® INDUSTRIES

P.O. Box 12
Merton, Wisconsin 53056
Phone: (262) 538-1122
www.essind.com