

www.essind.com

Eccothane™ LE

All Purpose Urethane Finish

Features

- Low emission formula – meets new 1% VOC Regulation
- Multi-surface, all-purpose urethane-fortified finish for all maintenance systems
- Improved formula for even smoother application
- Long-lasting, all maintenance, all surface floor finish
- Urethane-fortified for maximum durability and beauty
- Combination seal and finish
- Large area coverage – up to 3,000 sq. ft. per gallon
- For no buff, spray buff and ultra high speed burnish systems
- Use on vinyl tile, linoleum, terrazzo, rubber and quarry tile floors
- Slip-resistant – UL classified

Properties

Type..... Urethane / Acrylic Emulsion
Form..... Opaque Liquid
Odor..... Bland
Color..... Milky White
Weight per Gallon..... 8.60 Lbs
pH..... 7.5 - 8.5
Floor Solids..... 18%
Dry Time..... 30 Minutes
Storage Stability..... Min. 1 Year
Freeze/Thaw..... Do Not Freeze
V.O.C..... <1%



* Properties are typical and subject to usual manufacturing tolerances



Scan QR code for access to more product information and Safety Data Sheet.

71FF



ESSENTIAL
INDUSTRIES

P.O. Box 12
Merton, Wisconsin 53056
Phone: (262) 538-1122
www.essind.com

© 2019 Essential Industries, Inc. F2619

Lit. # LT-90000S0071FF