

Eccothane™ LE

All Purpose Urethane Finish

FEATURES

- Low emission formula – meets new 1% VOC Regulation
- Multi-surface, all-purpose urethane-fortified finish for all maintenance systems
- Improved formula for even smoother application
- Long-lasting, all maintenance, all surface floor finish
- Urethane-fortified for maximum durability and beauty
- Combination seal and finish
- Large area coverage – up to 3,000 sq. ft. per gallon
- For no buff, spray buff and ultra high speed burnish systems
- Use on vinyl tile, linoleum, terrazzo, rubber and quarry tile floors
- Slip-resistant – UL classified

PROPERTIES

Type: Urethane / Acrylic Emulsion

Form: Opaque Liquid

Odor: Bland

Color: Milky White

pH: 7.5 - 8.5

V.O.C.: < 1%

Weight per Gallon: 8.60 Lbs


Storage Stability: Min. 1 Year

Freeze/Thaw: Do Not Freeze

Dry Time: 30 Minutes

Floor Solids: 18%

Properties are typical and subject to usual manufacturing tolerances



71FF

© 2021 Essential Industries, Inc. A2221
Lit. # LT-90000S71FF



Scan QR code
for access to more
product information
and Safety Data Sheet.

 **ESSENTIAL®**
INDUSTRIES

P.O. Box 12
Merton, Wisconsin 53056
Phone: (262) 538-1122
www.essind.com