

www.xcoatnano.com

# X-Coat<sup>TM</sup> NANO 22

patented nano-zinc technology



86FF

## Performance Coating

## Extreme

### Features

- Incorporates our patented nano-zinc technology for more thorough and denser cross-linking of finish.
- Nano-zinc cross-linking provides superior:
  - Lay-down gloss
  - Durability
  - Soil resistance
  - Gloss build
  - Mark resistance
  - Dry and recoat times
- Ammonia-free for dramatically reduced odor.
- High solids formula offers greater protection with fewer coats.
- Ideal for limited maintenance programs, yet responds to daily burnishing, if desired.
- Low emissions formula - meets California's new 1% VOC Regulation.
- Fast-drying - 15-20 minutes under normal conditions.
- Slip-resistant - UL-classified

### Properties

**Type:** Acrylic Emulsion  
**Form:** Opaque Liquid  
**Odor:** Bland  
**Color:** Milky White  
**Film Clarity:** Clear  
**Weight Per Gallon:** 8.65 Lbs.

**pH:** 7.0 - 8.0  
**Floor Solids:** 22%  
**Storage Stability:** Minimum 1 Year  
**Freeze/Thaw:** Protect From Freezing  
**V.O.C.:** <1%

\* Properties are typical and subject to usual manufacturing tolerances



Scan QR code for access to more product information and Safety Data Sheet.

**ESSENTIAL<sup>®</sup>**  
**INDUSTRIES**

P.O. Box 12  
Merton, Wisconsin 53056  
Phone: (262) 538-1122  
www.essind.com

© 2021 Essential Industries, Inc. A2521  
Lit. # LT-90000S0086FF