

Green Strip

Environmentally-Responsible Floor Stripper



FEATURES


- Easily removes multiple coats of G2 Green Finish from any floor
- Phosphate-free, butyl-free and caustic-free
- Non-corrosive per DOT to offer user safety and simplified shipping
- Leaves no alkaline residue behind, simplifying rinsing and eliminating recoat problems
- High activity - over 30% for maximum cost benefits and reduced inventory
- VOC Content - 5%



PROPERTIES

Type: Solvent Stripper	pH at Use Dilution (1:4): 10.4
Form: Clear Liquid	Weight per Gallon: 8.76 Lbs
Odor: Characteristic	Storage Stability: Min. 1 Year
Color: Colorless	Freeze/Thaw: Passes 3 Cycles
Actives: 30%	Foam Height: Moderate
pH: 10.9	

Properties are typical and subject to usual manufacturing tolerances



8881FX

© 2021 Essential Industries, Inc. J2621
Lit. # LT-9000S8881FX



Scan QR code
for access to more
product information
and Safety Data Sheet.



P.O. Box 12
Merton, Wisconsin 53056
Phone: (262) 538-1122
www.essind.com

TRAINING

Green Strip

Environmentally-Responsible Floor Stripper

Environmentally preferable formula is butyl-free, caustic-free and phosphate-free. Non-corrosive per DOT to offer user safety and simplified shipping.

Directions

READ BEFORE USING

1. Dilute before using. Do not use on painted surfaces or wooden floors. Use cautiously for stripping linoleum, or rubber tile as stripper may cause bleaching, softening or bleeding.
2. Wipe up any spills or splashing from baseboards or painted surfaces immediately.
3. Dilute as instructed below. Stronger dilutions will not increase efficacy.

DIRECTIONS

1. Dilute with cold water as follows: 1 part stripper to 4 parts water.
2. Apply liberally to floor covering 100 square feet at a time. Be sure to leave surface VERY wet!
3. Allow to remain on floor 5 to 10 minutes. Agitate for 100% removal of old floor finish.
4. Pick up solution using a wet vac or auto-scrubber. If any finish remains (around baseboards), reapply stripping solution and agitate as necessary.
5. Rinse floor thoroughly. Allow floor to dry.
6. Apply G2 Green Finish.

NOTE: For stripping and maintaining asbestos containing tile, follow OSHA guidelines or EPA guidelines.



DISPOSAL

PRODUCT: Dispose of contents and container in accordance with all local, regional, national and international regulations.

CONTAINER: Please recycle container.

VENTILATION

No special ventilation needed. However, use of adequate ventilation is good industrial practice.

IMPROPER USE OR APPLICATION

IMPROPER USE: May irritate eyes, skin and gastrointestinal tract. Avoid eye and skin contact.

IMPROPER APPLICATION: Under dilution may affect product performance and may increase the risk of health effects. Over dilution may leave a residue and affect product performance.

WARNING

Causes skin irritation. Causes serious eye irritation. Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand. Wear protective gloves. Wear eye or face protection. Wash thoroughly after handling. Take off contaminated clothing and wash it before reuse.



FIRST AID:


IF ON SKIN: Wash with plenty of water. If skin irritation occurs: Get medical advice or attention. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice or attention.

See Product Safety Data Sheet Before Using.



8881FX

© 2021 Essential Industries, Inc. J2621
Lit. # LT-90000S8881FX



ESSENTIAL[®] INDUSTRIES

P.O. Box 12
Merton, Wisconsin 53056
Phone: (262) 538-1122
www.essind.com