

www.essind.com

X-CoatTM NANO

patented nano-zinc technology

NANO
technology
PATENTED
U.S. PATENT No.
8,236,903



88FF

Performance Coating

Extreme

Features

- Incorporates our patented nano-zinc technology for more thorough and denser cross-linking of finish.
- Nano-zinc cross-linking provides superior:
 - Lay-down gloss
 - Durability
 - Soil resistance
 - Gloss build
 - Mark resistance
 - Dry and recoat times
- Ammonia-free for dramatically reduced odor.
- Ideal for limited maintenance programs, yet responds to daily burnishing, if desired.
- Low emissions formula - meets California's new 1% VOC Regulation.
- Fast-drying - 15-20 minutes under normal conditions.
- Slip-resistant - UL-classified



Properties

Type: Acrylic Emulsion

Form: Opaque Liquid

Odor: Bland

Color: Milky White

Film Clarity: Clear

pH: 8.0 - 8.5

Weight Per Gallon: 8.57 Lbs.

Storage Stability: Minimum 1 Year

Freeze/Thaw: Protect From Freezing

V.O.C.: 0.59%

Properties are typical and subject to usual manufacturing tolerances



Scan QR code for access to
more product information
and Safety Data Sheet.

ESSENTIAL[®]
INDUSTRIES

P.O. Box 12
Merton, Wisconsin 53056
Phone: (262) 538-1122
www.essind.com

© 2023 Essential Industries, Inc. C1523
Lit. # LT-90000S0088FF