

SATIN SPORTKOTE®

POWERED BY ESSENTIAL POLYMERS

WATER-BASED URETHANE WOOD FINISH

FEATURES

- No sanding or screening
- Single-component — pour and apply
- No pot life
- Adheres to any sound gym floor coating
- Self cross-linking eliminates need for catalysts, gluing or heavy metals
- Fast-drying — 60 minutes under normal conditions
- Play on in the next day
- Easily restored to like-new gloss
- VOC-compliant in all 50 states
- Finish lasts at least a year with proper maintenance

PROPERTIES

Type: Urethane/Acrylic Blend

Form: Opaque Liquid

Odor: Bland

Color: Off-White

pH: 7.5 - 8.5

Weight per Gallon: 8.68 Lbs

Storage Stability: Min. 1 Year

Freeze/Thaw: Passes 3 Cycles

Floor Solids: 29%

V.O.C.: 274 gm/l

Floor Coating and
Finishing Material
As to Slip Resistance
Only. 177S



NEW AND
Now with Polycarbonate!

IMPROVED!

Properties are typical and subject to usual manufacturing tolerances

P.O. Box 12 | Merton, Wisconsin 53056-0012 USA | Phone: (262) 538-1122



228SF

Scan QR code
for access to
more product
information
and Safety
Data Sheet.



ESSENTIAL®
INDUSTRIES



www.essind.com