

www.essind.com

# X-Coat<sup>TM</sup> NANO 22 PLUS

patented nano-zinc technology



## 251FF Performance Coating

### Features

- Incorporates our patented nano-zinc technology for more thoroughly and denser cross-linking of finish.
- Nano-zinc cross-linking provides superior:
  - Lay-down gloss
  - Durability
  - Soil resistance
  - Gloss build
  - Mark resistance
  - Dry and recoat times
- Ammonia-free for dramatically reduced odor.
- High solids formula offers greater protection with fewer coats.
- Ideal for limited maintenance programs, yet responds to daily burnishing, if desired.
- Low emissions formula - meets California's new 1% VOC Regulation.
- Fast-drying - 20-30 minutes under normal conditions.
- Slip-resistant - Meets ASTM D2047

### Properties

**Type:** Acrylic Emulsion

**Form:** Opaque Liquid

**Odor:** Bland

**Color:** Milky White

**Film Clarity:** Clear

**pH:** 7.0 - 8.0


**Weight Per Gallon:** 8.60 Lbs.

**Storage Stability:** Minimum 1 Year

**Freeze/Thaw:** Protect From Freezing

**V.O.C.:** 0.57%

Properties are typical and subject to usual manufacturing tolerances



Scan QR code for access  
to Safety Data Sheet.

**ESSENTIAL<sup>®</sup>**  
**INDUSTRIES**

P.O. Box 12  
Merton, Wisconsin 53056  
Phone: (262) 538-1122  
www.essind.com

© 2025 Essential Industries, Inc. D0725  
Lit. # LT-90000S0251FF