

# G2

## High Performance Floor Coating

# Green Finish Gen 2

## Product Features

- Not formulated with butyl, harsh alkalies, zinc, phthalates or APEO surfactants
- Ultra-low 1.0% VOC content meets California's new 2011 standard
- Low odor - ammonia-free
- Multi-surface, all-purpose formula for all maintenance systems
- Easy-to-apply, levels nicely and dries to a high gloss
- Combination seal and finish
- Large area coverage – up to 3,000 sq. ft. per gallon
- Fast-drying – 20 minutes under normal conditions
- Meets ASTM D2047 Method for slip resistance
- Contains NO intentionally added PFAS



## Properties

- |                                 |   |
|---------------------------------|---|
| • <b>Type:</b> Acrylic Emulsion | • <b>pH:</b> 7.1 - 8.1                  |
| • <b>Form:</b> Opaque Liquid    | • <b>Weight per Gallon:</b> 8.60 Lbs.   |
| • <b>Odor:</b> Bland            | • <b>Storage Stability:</b> Min. 1 Year |
| • <b>Color:</b> Milky White     | • <b>Freeze/Thaw:</b> Do Not Freeze     |
| • <b>Film Clarity:</b> Clear    | • <b>V.O.C.:</b> 0.6%                   |

Properties are typical and subject to usual manufacturing tolerances.





# TRAINING

High Performance Floor Coating

# G2 Green Finish Gen 2

8205FF

## Directions

**NOTE:** Before use of this product, strip floor with a Green-Seal certified stripper, such as Green Strip.

### APPLICATION:

1. Strip floors to remove old waxes, sealers and finishes.
2. Rinse thoroughly and let dry.
3. With clean equipment apply thin, even coats of G2 Green Finish Gen 2.
4. Under normal conditions, allow to dry for 20 minutes between coats.
5. For best results, apply a maximum of 4 coats in 24 hours.
6. Allow 48 hours for the finish to reach full cure before wet cleaning.  
Burnishing will speed cure time.

**NOTE:** For stripping and maintaining asbestos containing tile, follow OSHA or EPA guidelines.

**COVERAGE:** One gallon covers up to 3,000 square feet.

### MAINTENANCE:

#### Daily:

1. Sweep or dust mop frequently to remove gritty soil.
2. Use our Green Clean to damp mop spills as they occur. Damp mop or auto-scrub nightly with Green Clean.
3. Buff if desired with high speed equipment and blended hair pads.

#### Weekly:

1. To repair and deep clean floor, apply a green restorer with mop or auto-scrubber.
2. Allow floor to dry.
3. Burnish floor with high speed equipment. This finish also responds to spray buffing with conventional speed equipment.

**Note:** Always dust mop after burnishing or spray buffing.


#### Periodic Recoating:

1. Dust mop entire floor then scrub aggressively using a restorer and auto-scrubber with a red or green pad.
2. Rinse floor and allow to dry.
3. Apply G2 Green Finish Gen 2.

**Stripping G2 Green Finish Gen 2:** Strip with Green Strip diluted 1:4.

#### Personal Protection Equipment

Gloves and Goggles



Not formulated with butyl, harsh alkalies, zinc, phthalates or APEO surfactants.

Read label before use. Keep out of reach of children. If medical advice is needed, have product container or label at hand.

### DISPOSAL

**PRODUCT:** Dispose of contents and container in accordance with all local, regional, national and international regulations.

**CONTAINER:** Please recycle container.

### VENTILATION

No special ventilation needed. However, use of adequate ventilation is good industrial practice.

### IMPROPER USE OR APPLICATION

**IMPROPER USE:** May irritate eyes, skin and gastrointestinal tract. Avoid eye and skin contact.

**IMPROPER APPLICATION:** Over application of finish may cause floor to be tacky, streaked and/or ghosted looking, dull and prone to black marking and scuffing.

**NOTE:** DO NOT FREEZE

**See Product Safety Data Sheet Before Using.**



**ESSENTIAL<sup>®</sup>**  
**INDUSTRIES**

Merton, Wisconsin 53056-0012  
Ph: 262.538.1122 or 800.551.9679  
[www.essind.com](http://www.essind.com)

© 2025 Essential Industries, Inc. E0525  
LT-90000S8205FF