



PANTHEON

CONCRETE SEALER

FEATURES

- For interior applications
- Wet adhesion properties
- Low VOCs
- Non-blushing, non-yellowing
- Excellent water resistance
- Resistant to acids, bases and stains
- Formulated without intentionally added PFAs

STAIN RESISTANCE

1 Hour Test, 1 Hour Recovery

10W30 Synthetic Oil.....	No Effect
10W30 Motor Oil.....	No Effect
Silicone Brake Fluid.....	No Effect
Kerosene.....	No Effect
Coke.....	No Effect
Automatic Transmission Fluid.....	No Effect
Vinegar.....	No Effect
90 Weight Gear Oil.....	No Effect
Gasoline.....	No Effect
Diesel Fuel.....	No Effect
Hydraulic Fluid.....	No Effect
Windshield Fluid.....	Slight softening, recovers
1:1 Ethylene Glycol/Water.....	Slight softening, recovers
E85 (85% Ethanol, 15% Gasoline).....	Slight softening, recovers



Floor Coating and Finishing
Material As to Slip Resistance Only. 177S

PROPERTIES

Properties are typical and subject to usual manufacturing tolerances.

Type: Acrylic Emulsion

Form: Opaque Liquid

Odor: Bland

Color: White

Film Clarity: Clear

Weight Per Gallon: 8.6 Lbs.

pH: 7.1 - 8.4

Floor Solids: 25%

Viscosity (CPS): < 20 CPS

Storage Stability: Minimum 1 Year

Freeze/Thaw: Protect From Freezing

V.O.C.: < 1%



© 2025 Essential Industries, Inc. C1325

P.O. Box 12
Merton, Wisconsin 53056
Phone: (262) 538-1122
www.essind.com

Lit. # LT-90000S0273FC



Training Videos



SDS