



262FF



ESSENTIAL[®]
INDUSTRIES

www.essind.com

X COAT 22

HIGH SOLIDS EXTREME PERFORMANCE COATING

FEATURES

- Combines deep gloss, high durability and ease-of-use into one product
- High gloss acrylic polymers produce a beautiful, long-lasting shine to reduce maintenance
- Non-yellowing, low maintenance formula offers excellent black mark and scuff resistance
- Formulated without intentionally added PFAS
- Perfect for classrooms, patient rooms, offices and retail establishments
- Ideal for limited maintenance programs, yet responds to daily burnishing, if desired
- Fast drying – 30 minutes under normal conditions
- Use on vinyl, rubber, linoleum, terrazzo, quarry tile and sealed concrete floors
- Slip-resistant – Meets ASTM D2047 Method



PROPERTIES

Type: Acrylic Emulsion

Form: Opaque Liquid

Odor: Bland

Color: Milky White

Film Clarity: Clear

Weight per Gallon: 8.59 Lbs

Storage Stability: Min. 1 Year

Freeze/Thaw: Passes 3 Cycles

pH: 7.5 - 8.5

V.O.C.: 0.75%

Properties are typical and subject to usual manufacturing tolerances



Scan QR code
for access to more
product information
and Safety Data Sheet.



P.O. Box 12
Merton, Wisconsin 53056
Phone: (262) 538-1122
www.essind.com