



273CF

PANTHEON

CONCRETE SEALER

EXCELLENT ON
TERRAZZO!

FEATURES

- For interior applications
- Wet adhesion properties
- Low VOCs
- Non-blushing, non-yellowing
- Excellent water resistance
- Resistant to acids, bases and stains
- Formulated without intentionally added PFAs

STAIN RESISTANCE

1 Hour Test, 1 Hour Recovery

10W30 Synthetic Oil.....	No Effect
10W30 Motor Oil.....	No Effect
Silicone Brake Fluid.....	No Effect
Kerosene.....	No Effect
Coke.....	No Effect
Automatic Transmission Fluid.....	No Effect
Vinegar.....	No Effect
90 Weight Gear Oil.....	No Effect
Gasoline.....	No Effect
Diesel Fuel.....	No Effect
Hydraulic Fluid.....	No Effect
Windshield Fluid.....	Slight softening, recovers
1:1 Ethylene Glycol/Water.....	Slight softening, recovers
E85 (85% Ethanol, 15% Gasoline).....	Slight softening, recovers



Floor Coating and Finishing
Material As to Slip Resistance Only. 1775

PROPERTIES

Properties are typical and subject to usual
manufacturing tolerances.

Type: Acrylic Emulsion
Form: Opaque Liquid
Odor: Bland
Color: White
Film Clarity: Clear
Weight Per Gallon: 8.6 Lbs.
pH: 7.1 - 8.4
Floor Solids: 25%
Viscosity (CPS): < 20 CPS
Storage Stability: Minimum 1 Year
Freeze/Thaw: Protect From Freezing
V.O.C.: < 1%



Durable Sealer for
Interior Concrete
and Terrazzo Floors



ESSENTIAL[®]
INDUSTRIES

P.O. Box 12
Merton, Wisconsin 53056
Phone: (262) 538-1122
www.essind.com

Lit. # LT-90000S0273FC

© 2026 Essential Industries, Inc. 10326



Training Videos



SDS